

HOLD AUDIO  
SPRING 2



Digital Analog Converter (DAC)

泉二 Foobar2000/SACD Manual



## Foobar2000 Playback Settings (these are all optional)

Set the required files for playing DSD files and the foobar2000 player software to download this folder first in this network folder <http://pan.baidu.com/s/1pLgseWb>  
After downloading the folder, extract the compressed file and prepare for installation and setup.



- Open the decompressed foodbar2000 file, it is recommended to install it by default, until it is completed.

 foobar2000_v1.3.4	14/10/13 16:38	应用程序	3,740 KB
---	----------------	------	----------


- Double-Click to open the foobar2000 installation file:




Click the “NEXT >” button to continue the installation.




Click the “I Agree” button to proceed with the installation.




Here the installation type selects the default “Standard Installation”, do not select “Portable Installation” click the “Next>” button to continue the installation.



If necessary, select the installation folder by clicking on “Browse...” or use the default path (recommended) and click “Install” to proceed with the installation.



Here the software composition selects the default (Full) installation (recommended), click the “Install” button to continue the installation.




Installation in progress...




When you see the notification as shown on the left, the installation is complete, click the “Finish” button, Foobar2000 installation is complete.


## Foobar2000 plays SACD ISO settings

1. Install the ASIO plugin. Double-Click the “foo\_out\_asio” file to install it with the default settings until it is complete.


 foo_out_asio	14/11/25 15:52	foobar2000 Co...	183 KB
--	----------------	------------------	--------



The prompt dialog box shown on the left will pop up during the installation: Click the “Yes” button to continue the installation.




After the installation is complete, click the “OK” button to make the installation take effect.




The application change program will ask you to restart the Foobar2000 prompt dialog and click the “Confirm” button.

2. Install the “foo\_input\_sacd” file and install it with default settings until it is complete.


<input checked="" type="checkbox"/>  foo_input_sacd	13/11/11 15:35	foobar2000 Co...	157 KB
--	----------------	------------------	--------



The prompt dialog box shown on the left will pop up during the installation: Click the “Yes” button to continue the installation.




After the installation is complete, click the “OK” button to make the installation take effect.




The application change program will ask to restart the Foobar 2000 prompt dialog and click the “Confirm” button.

The Foobar 2000 must also be setup after the installation is complete. In the foobar2000 playback interface, click “File” to select “Preferences”, or press CTRL+P to open the preference interface.




Select the output device as “DSD:ASIO:HoloAudio ASIO Driver” via the path Playback/Output as shown above, Then click on the “Apply”button.





SACD output format settings. Set the parameters as shown in the figure below via the Tools/SACD and click on the “Apply” button.



At this point, all the settings are completed, click the “OK” button.